



IVR-L 100/24-2 Tc Me Dp

With its 100-litre container capacity and autonomous barrel pump, the IVR-L 100/24-2 Tc Me Dp is suited to vacuuming, separating and returning liquids containing solids such as metal shavings.





New drive head for increased safety, convenience and power

- The low weight of the drive head ensures easier handling during transport, emptying and servicing.
- Greater work safety during transport due to cable storage on the machine head.

3 Practical tilting chassis

Quick and easy emptying of the container: just tip backwards and you are done!

2 360° working radius

Clean in all directions thanks to the rotatable hose connection on the suction head. Tangle-free suction hose.

4 Safe accessory storage

Suction hose storage hook and defined accessory storage for a clean, tidy and ready-to-use machine.

TECHNICAL DATA AND EQUIPMENT





IVR-L 100/24-2 Tc Me Dp

- Tilting chassis
- Stainless steel casing and container
- Drum pump function

Technical data		
Order no.		9.987-887.0
EAN code		4054278275864
Current type	V / Hz	220-240 / 50-60
Air flow rate	$I/s / m^3/h$	148 / 532
Vacuum	mbar / kPa	235 / 23
Nominal diameter of connection		ID 50
Nominal diameter of accessory		ID 50 / ID 40

Equipment

Accessories in scope of delivery No

IVR-L 100/24-2 TC ME DP 9.987-887.0































		ı	1					_
					1			
		Order no.	Quantity	ID	Length / width	Price	Description	
Bood control		oraci iio.	Quantity	1.0	/ width	11100	Description	L
Bend, coated	۱ ،	1 6 000 000 0	14 -:(-)	LID 42	1 1		Dead accorded sheet also being the second state of	J
Bend, screw connection		6.902-202.0 6.902-201.0	1 piece(s)	ID 42			Bend, powder-coated steel, electrically conductive, with sta screw.	
Suction tube, coated	2	0.902-201.0	1 piece(s)	ID 52			Seren.	44
Suction tube, screw connection	ر ا	6.902-182.0	1 piece(s)	ID 42	750 mm		For floor cleaning in combination with bend (6.902-202.0)	Т
Soction tobe, screw connection)	0.902-162.0	1 piece(s)	10 42	730 111111		and DN 42 floor nozzles.	
	4	6.902-181.0	1 piece(s)	ID 52	850 mm		For floor cleaning in combination with bend (6.902-201.0)	†_
	,						and DN 52 floor nozzles.	
Floor nozzles								
Multi-purpose floor nozzle, wet/	5	6.902-185.0	1 piece(s)	ID 42	370 mm		Multi-purpose nozzle, width 370mm, DN 42	
dry	6	6.902-184.0	1 piece(s)	ID 52	370 mm		Multi-purpose nozzle, width 370mm, DN 52	
	7	6.902-186.0	1 piece(s)	ID 52	500 mm		Multi-purpose nozzle, width 500mm, DN 52	
Brush strip	8	6.903-067.0	2 -part		500 mm		Brush strip for multi-purpose nozzle 500 mm 6.902-186.0.	
Other nozzles								Ļ
Flexible nozzle, plastic	9	6.902-197.0	1 piece(s)	ID 42	220 mm		Nozzle, elastic, rubber, DN 42	
	10	6.902-196.0	1 piece(s)	ID 52	250 mm		Nozzle, elastic, rubber, DN 52	
	11	6.902-198.0	1 piece(s)	ID 72	260 mm		Nozzle, elastic, rubber, DN 72	
Elongated round nozzle, rubber	12	6.902-200.0	1 piece(s)	ID 42	315 mm		Suction nozzle, rubber, round, DN 42, length 315mm	
	13	6.902-199.0	1 piece(s)	ID 52	315 mm		Suction nozzle, rubber, round, DN 52, length 315mm	
Round brush, angled	14	6.902-193.0	1 piece(s)	ID 42			Suction brush, round 45°, DN 42	
	15	6.902-192.0	1 piece(s)	ID 52			Suction brush, round 45°, DN 52	
Straight suction and air nozzle	16	6.902-205.0	1 piece(s)	ID 42			DN 42 suction and air nozzle, straight version. For conven-	
							ient vacuuming of recesses and crevices of all kinds. Please	
Curriago brushos	17	6,002,204,0	1 nines(s)	ID 42	120 mm		note that a separate compressed air supply is required.	+
Surface brushes	17		1 piece(s)	ID 42	120 mm		Surface brush, width 120mm, DN 42	-
Surface nozzle, aluminium	18		1 piece(s)	ID 42	150 mm		Surface nozzle, aluminium, width 150mm, DN 42	
Toba costina annala	19	6.902-187.0	1 piece(s)	ID 52	150 mm		Surface nozzle, aluminium, width 150mm, DN 52	
Tube suction nozzle	20	6.902-207.0	1 piece(s)	ID 42			For cleaning tubes and other line systems with a diameter of up to 200 mm.	
Crevice tools		1					or up to 200 mm.	
Crevice nozzle, plastic	21	6.902-195.0	1 piece(s)	ID 42	290 ×		Crevice nozzle, plastics, long, DN 42, width 13mm	L
					13 mm			
	22	6.902-194.0	1 piece(s)	ID 52	340 ×		Crevice nozzle, plastics, long, DN 52, width 13mm	
Crovice perale plactic flevible	23	6.902-210.0	1 piece(s)	ID 42	13 mm 340 ×		Bendable plastic crevice nozzle (ID 42) with a nozzle width	+
Crevice nozzle, plastic, flexible	23	0.902-210.0	1 piece(s)	10 42	20 mm		of 20 mm. Ideal for flexible applications thanks to high	
					20 11111		manoeuvrability.	-
	24	6.902-211.0	1 piece(s)	ID 52	425 ×		Bendable crevice nozzle (ID 52) of plastic for flexible appli-	
					20 mm		cations, with a nozzle width of 20 mm.	Ш
Crevice nozzle, galvanised	25	6.902-189.0	1 piece(s)	ID 52	350 ×		Crevice nozzle, zinc-plated, width 25mm, DN 52	
6		5000 1000	4 . ()	15.40	17 mm		6 1 1 6 11 11 11 47 81 49	╀
Crevice nozzle, zinc coated, flexi- ble	26	6.902-190.0	1 piece(s)	ID 42	490 × 17 mm		Crevice nozzle, flexible, width 17mm, DN 42	
PVC hoses					17 111111			÷
Connection hose, PVC, screw con-	27	6.907-310.0	1 piece(s)	ID 42	3 m		Electrically conductive, accessory end rotary coupling, hose	П
nection	28		1 piece(s)	ID 42	5 m		with DN 42 connector at both ends	П
	29	6.907-312.0	1 piece(s)	ID 52	3 m		Electrically conductive, accessory end rotary coupling, hose	+=
	30	6.907-313.0	1 piece(s)	ID 52	5 m		with DN 52 connector at both ends	Ī
		1 515.5		1	1		1	

IVR-L 100/24-2 TC ME DP 9.987-887.0





























		Order no.	Quantity	ID	Length / width	Price	Description	
Suction hose, available by the metre, PVC, screw connection	31	9.980-645.0		ID 42			Suction hose available in bulk, PVC, ID 40; without tap adapters, max. 15 m.	
	32	9.980-646.0		ID 52			Electrically conductive, without connections, whole metres up to max. 15 m, price per metre, max. temperature 85 °C, for fine and light suction waste.	
EVA hoses								
Connection hose EVA, screw con-	33	9.988-088.0	1 piece(s)	ID 42	3 m		EVA material, electrically conductive, ID 42 connection at	
nection	34	9.988-089.0	1 piece(s)	ID 42	5 m		both ends, slit and accessory end hinge, highly flexible, for fine and light suction waste. IVC only as an extension hose, IVR only with reduction.	
	35	9.988-090.0	1 piece(s)	ID 52	3 m		EVA material, electrically conductive, DN 52 connection at	
	36	9.988-091.0	1 piece(s)	ID 52	5 m		both ends, slit and accessory end hinge, highly flexible, for fine and light suction waste. IVC only as an extension hose,	
PU hoses							IVR only with reduction.	
Connection hose, PU, screw connection	37	6.907-314.0	1 piece(s)	ID 42	3 m		Electrically conductive, accessory end rotary coupling, hose with DN 42 connector at both ends	
ccd.	38	6.907-315.0	1 piece(s)	ID 42	5 m		Electrically conductive, with accessory end rotary coupling, hose with DN 42 connector at both ends.	
	39	6.907-316.0	1 piece(s)	ID 52	3 m		Electrically conductive, accessory end rotary coupling, hose	
	40	6.907-317.0	1 piece(s)	ID 52	5 m		with DN 52 connector at both ends	
Suction hose, available by the	41	9.980-678.0		ID 42			Electrically conductive, without connections, whole metres	
metre, PU, screw connection	42	9.980-649.0		ID 52			up to max. 15 m, price per metre, max. temperature 80 °C, for liquids and abrasive solids.	
Suction hose, available by the metre, light PU, screw connection	43	9.980-679.0		ID 42			Electrically conductive, without connections, whole metres up to max. 15 m, price per metre, max. temperature 80 °C, for liquids and solids.	
	44	9.980-680.0		ID 52			Suction hose available in bulk, lightweight, PU (max. 15 m), ID 50, without tap adapters.	
Metal hoses								
Connection hose, ME-PU, screw	45	6.907-318.0	1 piece(s)	ID 42	3 m		Electrically conductive, accessory end rotary coupling, hose	
connection	46	6.907-319.0	1 piece(s)	ID 42	5 m		with DN 42 connector at both ends	
	47	6.907-320.0	1 piece(s)	ID 52	3 m		Electrically conductive, accessory end rotary coupling, hose	. 🗆
	48	6.907-321.0	1 piece(s)	ID 52	5 m		with DN 52 connector at both ends	
Suction hose, available by the	49	9.980-647.0		ID 42			Electrically conductive, without connections, whole metres	
metre, ME-PU, screw connection	50	9.980-707.0		ID 52			up to max. 15 m, price per metre, max. temperature 110 °C, for metal shavings with liquids.	· _
Adapters and spare parts								
Reducer ID 52 to ID 42	51	6.902-179.0	1 piece(s)	ID 52			Reducer from ID 52 to ID 42.	
Hose connection	52	6.902-170.0	1 piece(s)	ID 42			For attachment to hose DN 42	
	53	6.902-168.0	1 piece(s)	ID 52			For attachment to hose DN 52	
Hose connection, rotatable	54	6.902-172.0	1 piece(s)	ID 42			Rotatable, for attachment to hose DN 42	
	55	6.902-169.0	1 piece(s)	ID 52			Rotatable, for attachment to hose DN 52	
Hose clamp	56	6.902-167.0	1 piece(s)	ID 42			For attaching hose to accessory connection DN 42/52	
Hose sleeve	57	6.902-171.0	1 piece(s)	ID 42			For attaching hose to accessory connection DN 42	
	58		1 piece(s)	ID 52			For attaching hose to accessory connection DN 52	
Star grip M 6	59	6.303-555.0	1 piece(s)	ID 42			M 6 star knob, replacement for all bends and connectors ID 42.	

[☐] Available accessories.

IVR-L 100/24-2 TC ME DP 9.987-887.0































		Order no.	Quantity	ID	Length / width	Price	Description	
Accessory kit IVR (1 phase)						_		۲
Vacuuming kit for liquids, screw connection	60	9.986-271.0	6 -part	ID 42			Reducer ID 52 to ID 42 (6.902-179.0), PU suction hose, 3 m, ID 42 (6.907-314.0), bend ID 42 (6.902-202.0), suction tube, 750 mm, ID 42 (6.902-182.0), floor nozzle, 370 mm, ID 42 (6.902-185.0), elongated round nozzle, rubber, ID 42 (6.902-200.0).	
Vacuuming kit for liquids and swarf, screw connection	61	9.986-280.0	6 -part	ID 42			Reducer ID 52 to ID 42 (6.902-179.0), ME-PU suction hose, 3 m, ID 42 (6.907-318.0), bend ID 42 (6.902-202.0), suction tube, 750 mm, ID 42 (6.902-182.0), floor nozzle, 370 mm, ID 42 (6.902-185.0), flexible nozzle, plastic, ID 42 (6.902-197.0).	
Vacuuming kit for liquids, screw connection	62	9.986-281.0	5 -part	ID 52			PU suction hose, 3 m, ID 52 (6.907-316.0), bend ID 52 (6.902-201.0), suction tube, 850 mm, ID 52 (6.902-181.0), floor nozzle, 370 mm, ID 52 (6.902-184.0), flexible nozzle, plastic, ID 52 (6.902-196.0).	
Vacuuming kit for liquids and swarf, screw connection	63	9.986-282.0	5 -part	ID 52			ME-PU suction hose, 3 m, ID 52 (6.907-320.0), bend ID 52 (6.902-201.0), suction tube, 850 mm, ID 52 (6.902-181.0), floor nozzle, 370 mm, ID 52 (6.902-184.0), surface nozzle, aluminium, ID 52 (6.902-187.0).	
Suction nozzles								Π
Vacuum brush	64	9.981-911.0	1 piece(s)	ID 42	300 mm		Vacuum brush, 300 mm, with 45° connection, with star	Г
	65	9.981-912.0	1 piece(s)	ID 52	300 mm		screw, horsehair bristles.	
Crevice nozzle, zinc coated, flexible	66	9.981-423.0	1 piece(s)	ID 42	490 × 20 mm		Crevice nozzle, steel, zinc coated, flexible, slit width 20 mm.	
	67	9.981-425.0	1 piece(s)	ID 52	490 ×			
Nozzle, zinc coated, flexible, with	68	9.981-420.0	1 piece(s)	ID 42	20 mm		Round nozzle, steel, zinc coated, flexible, with rubber tip DN	_
rubber tip	69	9.981-421.0	1 piece(s)	ID 52	30 mm		30.	F
Suction and air nozzle, 90° angled	70	9.981-926.0	1 piece(s)	ID 42	30 11111		DN 40 suction and air nozzle, 90° corner version. For convenient vacuuming of recesses and crevices of all kinds. Please note that a separate compressed air supply is required.	
Adapters and spare parts			'				1.1.	
Hose connection	71	9.981-260.0	1 piece(s)	ID 42			For attachment to hose ID 42, with slit and hook for hose attachment.	
	72	9.981-261.0	1 piece(s)	ID 52			For attachment to hose ID 52, with slit and hook for hose attachment.	Г
Accessories connection	73	9.981-325.0	1 piece(s)	ID 52			Rotatable, for attachment to hose ID 52, inner taper for attaching accessories.	
Y-adapter ID 52 to 2 × ID 42	74	9.981-149.0	1 piece(s)	ID 52			Hose pipe ID 50/40/40; external cone ID 50 on 2 \times internal cone ID 40.	
Suction container and swarf basket	s			,				
Swarf basket 40 l	75	9.980-849.0	1 piece(s)		495 mm		Strainer basket, stainless steel, 40 l, hole diameter 1.5 mm.	
Fine fleece, 40 l swarf basket	76	9.981-048.0	1 piece(s)		465 mm		Fine polyester fleece for separating fine metal shavings and liquids. With clamping ring suitable for 40 l swarf basket.	
Float insert	77	9.982-117.0	1 piece(s)		540 mm		Float insert, stainless steel, for overfill prevention with ball float, central suction.	

[☐] Available accessories.